



Bobcat T650

Engine

Emissions Tier (EPA)	Interim Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	55.4 kW
Turbocharged Engine	<input checked="" type="checkbox"/>

Performance

Rated Operating Capacity (ISO)	1166 kg
Operating Capacity (50% of Tip)	1665 kg
Tipping Load	3331 kg
Operating Weight	4282 kg
Travel Speed	10.6 km/h
Travel Speed (2-speed option)	17.2 km/h
Ground Pressure (Rubber)	0.4 bar

Capacities

Fuel Tank	103 l
-----------	-------

Hydraulic System

System Relief @ Quick Couplers	241.32 bar
Auxiliary Std Flow	87.1 l/min
Auxiliary High Flow	115.5 l/min

Dimension

Length	2753 mm
Length without Attachment	2753 mm
Length with Standard Bucket	3475 mm
Width	1852 mm
Width (with bucket)	1880 mm
Height	2065 mm
Height with Operator Cab	2065 mm
Height to Bucket Hinge Pin	3150 mm
Reach @ Maximum Height	869 mm
Turning Radius	2228 mm
Length of track on ground	1499 mm
Track Width	320 mm
Track Width - Optional	450 mm

Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	<input checked="" type="checkbox"/>
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>
Power Qtach	<input checked="" type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.