

T770 Loader Specifications

Engine

| | |
|----------------------|--------|
| Emissions Tier (EPA) | Tier 4 |
| Engine Cooling | Liquid |
| Engine Fuel | Diesel |
| Horsepower | 92 hp |
| Turbocharged Engine | |

Performance

| | |
|---------------------------------|----------|
| Rated Operating Capacity (ISO) | 3,475 lb |
| Operating Capacity (50% of Tip) | 4960 lb |
| Tipping Load | 9929 lb |
| Operating Weight | 10515 lb |
| Travel Speed | 6.6 mph |
| Travel Speed (2-speed option) | 10.7 mph |
| Ground Pressure (Rubber) | 4.2 psi |

Capacities

| | |
|-----------|----------|
| Fuel Tank | 43.8 gal |
|-----------|----------|

Hydraulic System

| | |
|--------------------------------|--------------|
| System Relief @ Quick Couplers | 3,500 psi |
| Auxiliary Std Flow | 23 gal/min |
| Auxiliary High Flow | 36.6 gal/min |

Dimension

| | |
|-----------------------------|----------|
| Length | 141.6 in |
| Length without Attachment | 114.3 in |
| Length with Standard Bucket | 141.6 in |
| Width | 78 in |
| Width (with bucket) | 80 in |
| Height | 81.3 in |
| Height with Operator Cab | 81.3 in |
| Height to Bucket Hinge Pin | 131.4 in |
| Reach @ Maximum Height | 35.2 in |
| Turning Radius | 88 in |
| Length of track on ground | 63.7 in |
| Track Width | 17.7 in |

Source: <https://www.bobcat.com/loaders/compact-track-loaders/models/t770/specs-options>